

Durox Self-Torquing Fuel Site Bowl Clevis & Seal Kit

The original design of the fuel site bowl clevis requires users to make a judgment call as to how much torque to apply. Too tight and the glass bowl cracks, too loose and the application leaks - either can result in a fuel leak. In addition, the simple design of the square cut gasket used for the fuel site bowl seal easily allows the bowl to slide off, which also causes leaks.

- **Durox #DE13527: Self-Torquing Clevis** tightens until the proper torque limit is reached and then spins harmlessly, totally eliminating the possibility of under or over-torquing the application.
- **Durox #DE10864: Fuel Sight Bowl Seal** is contoured so that the bowl fits into the seal and eliminates the possibility of it slipping and leaking.
- **Durox #DE32515: Self-Torquing Fuel Sight Bowl Clevis & Seal Kit** eliminates all problems that are associated with this application and will remain “leak free” from overhaul to overhaul.



Durox Governor Plug Protector

Governor plug failures are often caused by oil and dirt from normal engine operation, strong cleansers and high-pressure water and steam used for engine cleaning; all which can penetrate governor plugs and cause the connectors to short out. The Durox Governor Plug Protector:

- Provides a water-tight seal.
- Protects the plug from penetration by disruptive elements.
- Helps support the cable to relieve stress on the plug connection.
- Is easily installed in the field using the installation tool without removing the plug from the cable.

Durox #	Description
DE3829	Kit, 16 PIN
DE3613	Protector, 16 PIN
DE3810	Kit, 12 PIN
DE3807	Protector, 12 PIN
DE3826	Collar
DE3891	Kit, Collar
DE3619	Installation Tool
DE3615	Kit, Internally Mounted

